

Corn Cooking Optimization

From Kernel to Finished Product — A Technical Deep Dive

Nicolas Charalampidis — Head of R&D, Baking and Laboratory, Americas




Agenda

- The corn kernel: structure & composition
- Corn quality and handling
- Cooking: traditional vs. Industrial
- Milling
- Gums & enzymes: general effects
- Troubleshooting & quality control
- Key takeaways



Corn Kernel Anatomy


- Pericarp: outer fiber layer, protects the kernel
- Endosperm: the bulk of the kernel, mostly starch
- Germ: embryo, rich in oil and protein
- Pedicel / Tip Cap: attachment point to the cob



Kernel Composition by Component

- Endosperm: ~83% starch
- Germ: ~11% fat / protein
- Pericarp: ~5% fiber
- Pedicel / Tip Cap: ~1% fiber

Distribution changes behaviour under heat and alkaline change



Starch, Protein & Lipid Distribution

- Starch (endosperm): governs gelatinization and dough body
- Protein (germ & endosperm): structural, generally lower quality protein
- Lipids (germ): under 5% of kernel, rich in oleic & linoleic acid
- Vitamins/minerals concentrated in the germ



How do kernels break during the cooking process?

- Heat + alkali loosen the pericarp
- Starch begins to gelatinize in the outer endosperm
- Structure softens, enabling water penetration
- Sets up the kernel for steeping and milling



Corn Quality: Why It Matters

- Inconsistent corn = inconsistent cook, steep, and yield
- Poor-quality kernels absorb water unevenly
- Quality issues surface downstream: milling, machinability, shelf life
- 90% of problems can be caught at intake, before cooking



Grading Factors: Test Weight & BCFM

- Test weight (density): baseline physical quality indicator
- BCFM: Broken Corn & Foreign Material, measured by sieve
- max 3% brakeage, max 5% total damage
- Moisture content affects storage stability and cook uniformity



Common Kernel Defects

- Broken and cracked kernels, mechanical damage in handling
- Insect-damaged kernels
- Heat / fire damage from drying
- Mold and fermented kernels, food-safety risk
- Foreign material: stones, husk, chaff



Pre-Cleaning Before Cooking

- Removes stones, dust, chaff, and light foreign material
- Reduces broken kernels and fragments reaching the cook step
- Improves aeration and storage stability
- Catches most quality issues before they cost you a batch



Handling Substandard Corn

- Screen and segregate by grade at intake
- Set clear rejection thresholds (moisture, BCFM, damage %)
- Blend cautiously, defects don't average out evenly
- Document and feed back to sourcing/suppliers



Why We Cook Corn?

- Gelatinizes the starch
- Builds a cohesive dough at the mill
- Under-cooked masa lacks structure: problems at the sheeter/cutter
- Cooking quality is the foundation for everything downstream



Two Paths: Traditional vs. Industrial

- Traditional cooking: heat + water, lime
- Alkali loosens the pericarp and softens the endosperm
- Nixtamalization is the standard for tortillas and masa producers




Nixtamalization process

	<u>Traditional</u>	<u>Industrial</u>
• Time	1 – 2 h	40 – 45 min
• Lime	1 – 2 %	0.1 – 0.4 %
• Resting time	8 – 16 h	4 - 6 h

Process Flow Overview

- Cooking → Steeping → Washing/Rinsing → Milling/Grinding → Masa
- Each step corrects and refines what came before
- A weakness at any stage shows up at the sheeter or in the final product



Cooking Parameters: Ratio & Rise Time

- Reference ratio
corn : water : lime $\approx$ 100 : 200 : 1-2
- Rise to reach $\sim 195^{\circ}\text{F}$
- Rate of temperature rise affects uniformity across the batch
- Rate of temperature Drop affects uniformity across the batch



Cooking Temperature & Time: Traditional vs. Industrial

- Traditional: 1–2 h cook, 1–2% lime, 8–16 h resting
- Industrial: up to 45 min cook, 0.1–0.4% lime, 4–6 h resting
- Cook window: 180–195°F (82–91°C) for 3–30 minutes
- Industrial process trades time for tighter process control



Cooking QC: Agitation, pH & Lime

- Corn is still “cooking” at or above 140°F (60°C)
- Check agitation and heat uniformity across the kettle
- Measure pH and adjust lime level as needed
- Adjust time/temperature as ambient conditions change



Cooling the Batch: The 60°C Threshold

- Corn continues cooking as long as it's at/above 140°F (60°C)
- Time to drop below 60°C: typically 30–90 minutes
- Below this threshold, the corn is steeping — not cooking
- This transition point is what defines an even, repeatable batch




Achieving an Even Cook

- Consider quenching to shorten cooling time
- Uniform agitation avoids hot/cold pockets in the kettle
- Consistent cool-down = consistent steep = consistent masa
- Batch-to-batch repeatability starts here



Cooking Adjustments: Over vs. Undercook

- Relative overcook (tortillas): softer, more pliable masa
- Relative undercook (chips): drier masa, absorbs less frying fat
- How to tell: texture, color, and grind resistance of the nixtamal
- The target cook point depends on the end product



Steeping: Purpose

- Corn must be below 140°F (60°C) to be steeping, not cooking
- Allows water and lime to diffuse into the grain structure
- Pericarp detaches from the corn during this stage
- Result: softer, more uniform kernels at the grinder



Steeping Time: Range & Risks

- Reference range: 3 to 16 hours
- Too short: incomplete hydration, harder grind, uneven masa
- Too long: over-softened kernel, yield and handling issues
- Steeping time is a lever, not a fixed constant



Washing / Rinsing: Purpose & Parameters

- Removes loose pericarp, excess lime, and nejayote (liquid residue)
- Typical parameters: 40–60 RPM, ~80 psi spray, ~30 seconds
- Target moisture in the nixtamal
- The simple test: does it feel “squeaky” clean?



Washing's Impact on Quality

- Affects pH, flavor, color, and yield
- Reduces nixtamal temperature toward ~80°F (27°C)
- Under-washed: excess pericarp, high pH, dark color
- Over-washed: product loss, low pH, overly light color



Milling: Process & Equipment

- Traditional stone grinders (volcanic stone)
- Steel grinding stones,
- This is where preservatives or other ingredients can be added
- Milling converts nixtamal into raw masa



Hammer Milling vs. Stone Grinding

- Hammer milling: typically for dried flour production
- Stone grinding: traditional route, direct to fresh masa
- Choice impacts particle size distribution and starch damage
- Equipment choice should match the target flour type



Particle Size Control

- Particle size drives water absorption and machinability
- Coarser grind → lower absorption, more “snack” character
- Finer grind → higher absorption, more “tortilla” character
- Temperature rise at the mill should stay low as possible



How Cooking Conditions Influence Milling

- Under-cooked corn: harder grind, more wear on equipment
- Over-cooked corn: softer, easier grind, but may lose structure
- Cook/steep consistency directly drives grind consistency
- Milling can't fully correct an inconsistent cook



From Nixtamal to Masa: What Changes

- Mechanical shear ruptures starch granules and releases surface starch
- This surface starch is what gives masa its cohesiveness
- Masa is ready shortly after grinding, with some floor time (5–10 min)




Masa Quality Markers

- Moisture: target range depends on product (tortilla vs. chip)
- Temperature: affects handling and shelf behaviour at the sheeter
- Cohesiveness: the practical test of a well-cooked, well-milled batch



Water Absorption & Particle Size by Flour Type

- Tortilla flour: ~120–140% water absorption
- Snack flour: ~60–100% water absorption
- Cooking grade and particle size are the main levers behind this gap
- This single variable reshapes downstream mixing and machinability



From Masa to Dough: The Mixing Step

- Sigma-blade mixer, masa flour plus water
- Tortillas: more water than flour
- Chips: less water than flour
- Mix to incorporation: dough temperature and consistency is a key control point



Sheeting: How Masa Moves Through the Rollers

- Dough is fed onto a sheeting/laminating line
- Rollers compress the dough to a uniform thickness
- Cutters portion the sheet into individual pieces
- Sheet uniformity directly determines final product uniformity



Roller Type & Dough Temperature

- Plastic or stainless-steel roller heads, different release behaviour
- Ambient dough temperature can be enough, no warm/hot water required
- Correct roller/dough-temperature pairing improves machinability
- This is a frequent, low-cost lever for line performance



Common Machinability Challenges

- Dough sticking to rollers or cutters
- Inconsistent sheet thickness feeding downstream
- Tearing or poor edge definition at the cutter
- Most of these trace back to cook, steep, or grind, not the sheeter itself




Cooking Your Own Corn vs. Using Masa Flour

- Cooking your own corn: “signature” masa, more control, lower commodity cost
- Masa flour: convenient, no wastewater issues, less equipment/space
- Masa flour also means fewer ingredients to inventory
- The right choice depends on plant scale and flexibility needs




Beyond the Base Process: Functional Ingredients

- Gums and enzymes are used to fine-tune what cooking and milling deliver
- They work on the same variables we've covered: water, starch, structure
- The next slides cover general mechanisms only, not specific formulations



Hydrocolloids (Gums): General Role

- Bind water and modify dough viscosity
- Can improve cohesiveness in lower-absorption (snack-type) doughs
- Support texture retention over shelf life
- Effect depends heavily on gum type and inclusion level



Force (g)

Elasticity (mm)

Reference. No additives

595

18.3



Hydrocolloid and enzyme mix

929

23.3



Enzyme Categories in Corn Processing

- Amylase: breaks down starch chains
- Protease: breaks down protein structure
- Lipase: acts on fats/lipids
- Hemicellulase: acts on fiber/cell-wall components (not pictured)



General Effects on Dough Rheology

- Can shift torque/consistency curves (amylogram response)
- May soften dough or reduce mixing time needed to reach target consistency
- Changes are measurable via standard rheology testing
- Effect size is formulation- and dose-dependent




General Effects on Texture & Shelf Life

- Can influence crumb/crunch texture in the finished product
- May support moisture retention over storage time
- Can reduce staling-type texture changes
- Always evaluated against baseline (no-enzyme) product



Enzyme–Gum Synergy: The Concept

- Enzymes modify starch/protein structure; gums modify water binding
- Combined, they can address more than either alone
- Synergy is evaluated through rheology and sensory testing
- Not all combinations are synergistic testing drives the decision



	Force (g)	Elasticity (mm)
Reference. No additives	595	18.3
Hydrocolloid and enzyme mix	929	23.3

Considerations When Balancing Functional Ingredients

- Match the tool to the defect don't over-correct
- Dosage interacts with cook, steep, and grind conditions
- Validate with the same tests used for base-process QC
- Document formulation changes alongside process changes



Process Control Checkpoints: Tortilla Line

- Quality of nixtamal/masa: corn specs, cook profile, steep, particle size, moisture, pH
- Masa feeder and sheeter weight adjustments
- Oven conditions
- Cooling conditions
- Counterstacker and packaging



Process Control Checkpoints: Chip Line

- Quality of nixtamal/masa
- Masa feeder and sheeter
- Oven conditions
- Equilibration/moisture before frying
- Frying time, temperature, and condition of fat (FFA)
- Coating application and packaging seal





Factors Influencing Color

- Type of corn
- Quality of rinsing
- pH
- Baking/frying time and temperature
- Condition of frying fat
- Packaging



Factors Influencing Texture

- Quality of corn and quality of cook/steep
- Finished product moisture
- Finished product fat content (chips)
- Traces back through the whole process, not just the final step



Factors Influencing Flavor & Aroma

- Quality of corn
- Quality of cooking, steeping, and rinsing
- pH
- Amounts and types of preservatives
- Quality of frying fat and topping coverage (chips)



Key Takeaways: Process

- Cook and steep control set the ceiling for everything downstream
- The 60°C cooling threshold is what makes a batch repeatable
- Milling and mixing can refine, but can't fix a poor cook
- Process consistency beats any single parameter change



Key Takeaways: Ingredients & Quality

- Incoming corn quality drives everything screen it seriously
- Gums and enzymes are fine-tuning tools, not fixes for a broken process
- Every functional ingredient decision should be tested against baseline
- Troubleshooting works backward: defect → process step → root cause



Conclusions

- Corn cooking optimization spans kernel, cook, mill, and mix
- Traditional and industrial nixtamalization share the same fundamentals
- Small process shifts (cook time, steep time, cooling rate) compound downstream
- Consistency, not intensity, is the real lever





deutscheback

Together. Better Baking.

**Thank you very much for your attention
Nicolas Charalampidis**

ncharalampidis@sterningredients.com.mx

cel. +525559092248